

# V606

## DECORATIVE EXPANSION JOINT



### Product Description

Decorative expansion joints or so-called Pipe Expansion Joints absorb axial movement and secures the pipeline. Mostly preferred at in-house building HVAC applications and some industries that needs expansion.



Technical Data	
Size range	DN15 - DN100
Pressure range	PN16
Temperature	-10°C to +100 °C
Design	EN 14917 & EJMA
Face to face	EN 14917
Connection Standard	Threaded
Testing	EN 12266-1
Marking	EN 19
Expansion Range	50 mm.

### Application Range

- HVAC lines
- Hot & Cold Water
- Industrial Applications

### Related Products

- V60 Series Expansion Joints



HVAC



POTABLE WATER

### Product Features

- Inside building piping installations, absorbs line movements. Advised to be used one for each 30 meters (10 floors).
- Absorb noises and maintains peaceful environment
- Can absorb axial movements due to thermal differences
- Highly flexible, very compact and almost unnoticeable design
- Helps to protect piping elements due to misalignment
- It consists SS bellows and accompanying threads
- With its limit pin, the expansion rate can easily be observed

### Dimension Table

Nominal Size		L (mm.)	D	Pressure (bar)
		Expansion Range (mm.)		
DN	Inch	50		
15	1/2"	260	35	16
20	3/4"	260	42	
25	1"	260	51	
32	1 1/4"	260	60	
40	1 1/2"	260	63	
50	2"	260	70	
65	2 1/2"	260	99	
80	3"	260	114	
100	4"	260	139	